


## **DISCS WITH ADHESIVE**



Magnets with adhesive are a suitable alternative to glue or screws. They are usually available with the adhesive glued both on North and South face. It's recommended to respect the max operating temperatures indicated in Physical Magnet Data Sheet. .

All measurements are in millimeters. Other sizes and shapes on request.

The strength of attraction is purely indicative and it could be different depending on the type of application and assembly.

The magnetization is axial. Other kind of magnetization on request.

CODE	TYPE	DIAMETER	Н	STRENGTH KG
OODL		DIAMETER		STRENGTING
DN01.35NI00.101AD	SC35MANI	10	1	0,40
DN01.35NI00.101.5AD	SC35MANI	10	1,5	0,45
DN01.35NI00.102AD	SC35MANI	10	2	1,10
DN01.35NI00.120.75AD	SC35MANI	12	0,75	0,55
DN01.35NI00.121.5AD	SC35MANI	12	1,5	1,00
DN01.35NI00.122AD	SC35MANI	12	2	1,53
DN01.35NI00.140.5AD	SC35MANI	14	0,5	0,45
DN01.35NI00.141AD	SC35MANI	14	1	0,84
DN01.35NI00.144AD	SC35MANI	14	4	3,40
DN01.35NI00.151AD	SC35MANI	15	1	0,76
DN01.35NI00.151.5AD	SC35MANI	15	1,5	1,10
DN01.35NI00.152AD	SC35MANI	15	2	1,50
DN01.35NI00.153AD	SC35MANI	15	3	2,70
DN01.35NI00.161AD	SC35MANI	16	1	0,86
DN01.35NI00.201AD	SC35MANI	20	1	1,03
DN01.35NI00.201.5AD	SC35MANI	20	1,5	1,80
DN01.35NI00.202AD	SC35MANI	20	2	2,30
DN01.35NI00.203AD	SC35MANI	20	3	3,50